

## Foret en carbure monobloc - à lubrification interne

B1

Profondeur de perçage	5 x D <sub>C</sub>	5 x D <sub>C</sub>



Désignation	DC160 Advance X-treme Evo	DC160 Advance X-treme Evo	DC150 Perform	DC150 Perform	DB133 Supreme
Autres services					
Norme	DIN 6537 L	DIN 6537 L	DIN 6537 L	DIN 6537 L	Walter
Revêtement / nuance	WJ30ET	WJ30ET	WJ30RE	WJ30RE	WJ30EL
Queue	DIN 6535 HA	DIN 6535 HE	DIN 6535 HA	DIN 6535 HE, pivoté de 180° DIN 6535 HB	DIN 6535 HA
Plage de Ø [mm]	3-25	3-25	3-20	3-20	0,7-2,95
P Acier	●●	●●	●●	●●	●●
M Acier inoxydable	●	●	●	●	●●
K Fonte	●●	●●	●●	●●	●●
N Métaux non ferreux	●●	●●	●●	●●	●●
S Matériaux difficilement usinables	●●	●●	●●	●●	●●
H Matériaux durs	●	●	●	●	●
O Autres	●	●	●	●	●
Page dans le catalogue	B 37	B 41	B 45	B 48	B 53
Code QR					
www.walter-tools.com/woc/	DC160	DC160	DC150	DC150	DB133