


## J -Douilles 3/8" 12 pans métriques



### Description :

- Profil OGV® : plus de puissance et de sécurité, préserve les écrous.
- Disponible en jeu sur rack métallique (Réf J.40E : 7 --> 16 mm).
- Présentation : chromée brillante.

|  | A [mm] | Diamètre [mm] | Diamètre D1 [mm] | longueur [mm] | Longueur L1 [mm] | 12 points [mm] | Poids [g] |
|--|--------|---------------|------------------|---------------|------------------|----------------|-----------|
| <b>J.10</b>  | 10.0   | 17.6          | 14.7             | 27.0          | 7.8              | 12.0           | 26.0      |
| <b>J.11</b>  | 11.0   | 17.6          | 16.0             | 27.0          | 9.0              | 12.0           | 27.0      |
| <b>J.12</b>  | 12.0   | 17.6          | 17.2             | 27.0          | 9.5              | 12.0           | 26.0      |
| <b>J.13</b>  | 13.0   | 17.5          | 18.3             | 30.0          | 10.4             | 12.0           | 36.0      |
| <b>J.14</b>  | 14.0   | 17.7          | 19.5             | 30.0          | 10.5             | 12.0           | 34.0      |
| <b>J.15</b>  | 15.0   | 19.0          | 20.8             | 30.0          | 12.0             | 12.0           | 38.0      |
| <b>J.16</b>  | 16.0   | 20.0          | 22.0             | 30.0          | 12.0             | 12.0           | 45.0      |
| <b>J.17</b>  | 17.0   | 21.7          | 23.4             | 30.0          | 13.0             | 12.0           | 52.0      |
| <b>J.18</b>  | 18.0   | 21.7          | 24.7             | 33.0          | 13.0             | 12.0           | 69.0      |
| <b>J.19</b>  | 19.0   | 22.7          | 26.0             | 33.0          | 14.0             | 12.0           | 62.0      |
| <b>J.20</b>  | 20.0   | 22.2          | 27.2             | 33.0          | 15.0             | 12.0           | 70.0      |
| <b>J.21</b>  | 21.0   | 23.5          | 28.5             | 33.0          | 16.0             | 12.0           | 75.0      |
| <b>J.22</b>  | 22.0   | 24.7          | 29.7             | 33.0          | 16.5             | 12.0           | 80.0      |
| <b>J.23</b>  | 23.0   | 26.0          | 31.0             | 33.0          | 16.5             | 12.0           | 90.0      |
| <b>J.24</b>  | 24.0   | 26.3          | 31.3             | 33.0          | 16.5             | 12.0           | 86.0      |
| <b>J.7</b>   | 7.0    | 17.6          | 11.0             | 27.0          | 6.0              | 12.0           | 24.0      |
| <b>J.8</b>   | 8.0    | 17.6          | 12.2             | 27.0          | 6.5              | 12.0           | 25.0      |
| <b>J.9</b>   | 9.0    | 17.6          | 13.5             | 27.0          | 6.7              | 12.0           | 25.0      |