

Taper bushes
Metric bores - 1008 to 1310
Moyeux amovibles
Alésages métriques



Le moyeu amovible est l'interface entre l'arbre de transmission et de nombreux composants mécaniques. Fabriqués sur centres d'usinage automatisés :

- Positionnement angulaire des trous irréprochable
- Fonte haute résistance G3000
- Phosphatation pour résistance à la corrosion 200hbs
- alésage H7 et Ra√1.6
- Excellent maintien sur l'arbre
- Emballage individuel CMW plastifié et renforcé
- Vis et notice incluses.

Disponibles en "packs industriels" pour en faciliter la manipulation.

STOCK ET PRIX
SUR ITAFRAN.COM

Ø d mm	b mm	h mm	1008		1108		1210		1215		1310	
			Code	Masse kg	Code	Masse kg	Code	Masse kg	Code	Masse kg	Code	Masse kg
9	3	1,4	MX1008009	0,15	MX1108009	0,17						
10			MX1008010	0,15	MX1108010	0,17						
11	4	1,8	MX1008011	0,14	MX1108011	0,17	MX1210011	0,28	MX1215011	0,41		
12			MX1008012	0,14	MX1108012	0,16	MX1210012	0,28	MX1215012	0,41	MX1310012	0,33
14	5	2,3	MX1008014	0,13	MX1108014	0,16	MX1210014	0,27	MX1215014	0,39	MX1310014	0,32
15			MX1008015	0,13	MX1108015	0,15	MX1210015	0,27	MX1215015	0,39		
16			MX1008016	0,12	MX1108016	0,15	MX1210016	0,26	MX1215016	0,38	MX1310016	0,32
18			MX1008018	0,12	MX1108018	0,14	MX1210018	0,25	MX1215018	0,36	MX1310018	0,31
19	6	2,8	MX1008019	0,11	MX1108019	0,14	MX1210019	0,25	MX1215019	0,36	MX1310019	0,30
20			MX1008020	0,11	MX1108020	0,13	MX1210020	0,24	MX1215020	0,35	MX1310020	0,30
22			MX1008022	0,10	MX1108022	0,13	MX1210022	0,23	MX1215022	0,33	MX1310022	0,28
24			MX1008024	0,09	MX1108024	0,12	MX1210024	0,21	MX1215024	0,31	MX1310024	0,27
25	8		MX1008025	0,08	MX1108025	0,11	MX1210025	0,21	MX1215025	0,30	MX1310025	0,27
28					MX1108028 †	0,11	MX1210028	0,18	MX1215028	0,26	MX1310028	0,24
30							MX1210030	0,17	MX1215030	0,24	MX1310030	0,22
32							MX1210032	0,16	MX1215032	0,22	MX1310032	0,20
35	10	3,3									MX1310035	0,18
38												
40	12											
42												
45												
48												
De			35,0		38,0		47,5		47,5		51	
L	mm		22,2		22,2		25,4		38,1		25,4	
	pouce		7/8"		7/8"		1"		1 1/2"		1"	
Vis			HC 1/4" x 1/2"		HC 1/4" x 1/2"		HC 3/8" x 5/8"		HC 3/8" x 5/8"		HC 3/8" x 5/8"	

† : low key - Clavette basse. **h = 1,3 mm.**



Taper bushes
Metric bores - 1610 to 2517
Moyeux amovibles
Alésages métriques

Taper bush is the link between transmission shaft and numerous mechanical components. Manufactured on automated machining centre:

- impeccable angular positioning of holes
- high resistance G3000 casting
- black phosphating for resistance to corrosion 200HBS
- bored H7 and Ra√1.6
- excellent hold on shaft
- individual CMW plastic-backed packaging
- screws and manual included

Available in "industrial packs" to facilitate handling

STOCK AND PRICES
ON ITAFRAN.COM

Ø d mm	b mm	h mm	1610		1615		2012		2517 *			
			Code	Masse kg	Code	Masse kg	Code	Masse kg	Code	Masse kg		
14	5	2,3	MX1610014	0,42	MX1615014	0,61	MX2012014	0,81				
15			MX1610015	0,41	MX1615015	0,61	MX2012015	0,81				
16			MX1610016	0,41	MX1615016	0,60	MX2012016	0,80	MX2517016	1,73		
17							MX2012017	0,80				
18	6	2,8	MX1610018	0,40	MX1615018	0,58	MX2012018	0,79	MX2517018	1,71		
19			MX1610019	0,39	MX1615019	0,58	MX2012019	0,78	MX2517019	1,7		
20			MX1610020	0,39	MX1615020	0,57	MX2012020	0,78	MX2517020	1,69		
22			MX1610022	0,37	MX1615022	0,55	MX2012022	0,76	MX2517022	1,67		
24			8	3,3	MX1610024	0,36	MX1615024	0,53	MX2012024	0,74	MX2517024	1,65
25					MX1610025	0,35	MX1615025	0,52	MX2012025	0,74	MX2517025	1,63
28	MX1610028	0,33			MX1615028	0,48	MX2012028	0,71	MX2517028	1,59		
30	MX1610030	0,31			MX1615030	0,46	MX2012030	0,68	MX2517030	1,56		
32	10	3,3	MX1610032	0,30	MX1615032	0,43	MX2012032	0,66	MX2517032	1,53		
33			MX1610033	0,30			MX2517033	1,53				
35	12	3,8	MX1610035	0,30	MX1615035	0,38	MX2012035	0,62	MX2517035	1,48		
38			MX1610038	0,23	MX1615038	0,34	MX2012038	0,58	MX2517038	1,52		
40			MX1610040	0,22	MX1615040	0,32	MX2012040	0,56	MX2517040	1,38		
42			MX1610042	0,20	MX1615042 †	0,28	MX2012042	0,53	MX2517042	1,34		
45						MX2012045	0,48	MX2517045	1,27			
48	14	4,3				MX2012048	0,43	MX2517048	1,20			
50						MX2012050	0,39	MX2517050	1,15			
55	16	4,3						MX2517055	1,02			
60	18	4,4						MX2517060	0,87			
65									MX2517065	0,71		
De			57		57		70		85,5			
L	mm		25,4		38,1		31,75		44,45			
	pouce		1"		1 1/2"		1 1/4"		1 3/4"			
Vis			HC 3/8" x 5/8"		HC 3/8" x 5/8"		HC 7/16" x 7/8"		HC 1/2" x 1"			

† : low key - Clavette basse. **h = 2,2 mm.**

* : 2517 : available in steel, pilot bored 20mm. - Disponible sur stock en acier, préalésé à 20 mm.

